

# BK-05

## TAPING MACHINE FOR PACKING OF COMPONENTS INTO CARRIER TAPES

**KOMFI**<sup>®</sup>




- UNIVERSAL MODEL OF TAPING MACHINE SUITABLE FOR BOTH MANUAL TAPING AND AUTOMATED APPLICATIONS.
- MAY BE EASILY COMPLETED BY A VIBRATING BOWL OR INTEGRATED IN A THIRD PART'S PRODUCTION LINE.
- TAPE WIDTH ADJUSTABLE FROM 8mm TO 120mm.
- NO CHANGE OVER KITS NECESSARY!
- TAPE WIDTH ADJUSTMENT WITH INDICATOR, ACCURACY 0.1mm.
- SWINGING SEALING SHOES, TEMPERATURE AND PRESSURE ADJUSTABLE.
- CHANGEOVER WITHIN A FEW MINUTES WITHOUT TOOLINGS BY TRAINED OPERATOR.
- MICROMETER SCREWS FOR POSITION ADJUSTMENT OF THE SEALING SHOES AND COVER TAPE.
- PROGRAMMABLE COUNTER, PROGRAMMABLE TRAILER AND LEADER.
- SENSOR FOR COUNTING AND EMPTY POCKET RECOGNITION.
- HEAT SEAL AND PRESSURE SEAL POSSIBLE.
- INTERFACE FOR COMMUNICATION WITH PICK AND PLACE.
- SMOOTH MOVEMENT OF THE TAPE (ADJUSTABLE SPEED, ACCELERATION, DECELERATION).


TAPING MACHINE



Adjustment for tape width with indicator



Sealing shoes with micrometer screw



## OPTIONS

- Camera for marking and orientation.
- Cover tape sensor.
- Sensor for correct component position.
- Separated switchbox and operator panel for easy integration into line.

## CUSTOM BUILT-SOLUTIONS

- Possibility of individual machine modification based on specific requirements.

## TECHNICAL DATA

Dimensions:	2020 × 510 × 640 mm (L × W × H)
Weight:	76 kg
<b>Power:</b>	
Electrical:	230 V; 50 Hz; 0,7 kVa
Compressed air:	0,5 MPa
Speed:	0,5 sec. / cycle max.
Tape width:	8 mm - 56 mm (model A); 8 mm - 120 mm (model C)
Pocket depth:	23 mm max.
Interface:	RS232 /RS485 for remote controll Interface for Pick & Place Interface for Camera
Optical sensor:	Empty pocket Parts counter
Parameter / Heat seal:	Temperature, sealing time, pressure
Trailer / Leader:	Programmable

The technical parameters may change without prior notice. Find more details about the product and its technical parameters on [www.komfi.eu](http://www.komfi.eu).

### KOMFI spol. s r. o.

Dvořákova 1001  
563 01 Lanškroun  
Czech Republic  
[info@komfi.cz](mailto:info@komfi.cz)  
[www.komfi-industrial.com](http://www.komfi-industrial.com)